NAME OF MACHINEU-300	
INSTITUTION Joint Institute for	Nuclear Research
LOCATION Dubna, USSR	DATE 1972, same for 1975 **
.	
IN CHARGE G. N. Flerov	REPORTED by same
HISTORY AND STATUS	MAGNET
DESIGN, date1955MODEL tests	POLE FACE dia 310 cm; R ext 138 cm
DESIGN, date <u>1955</u> MODEL tests ENG. DESIGN, date <u>1956–1958</u>	GAP, min cm; Field kG
CONSTRUCTION, date 1956-1959	max 54 cm; Field $$ kG at 9×10^6
FIRST BEAM date (or goal int. 1960; ext. 1965	AVE FIELD at R max 16.7 kg A-turns
MAJOR ALTERATIONS none	CURRENT, STABILITY ± 100 parts/106
OPERATION, 150 hr/wk; On Target 120 hr/wk	$B \max/\langle B \rangle = 1.0$
TIME DIST., in house 95 %, outside 5 %	AVF SECTORS SPIRAL, max deg
USERS' SCHEDULING CYCLE weeks	POLE FACE coil pairs, AVF /sec
COST, ACCELERATOR	Harmonic 4 /sec; Rad Grad /sec, or
COST, FACILITY, total	circular; HEAVY ION, E max = $\frac{250}{q^2/A}$
FUNDED BY	WEIGHT, Fe 2090 , Cu, or Al 101 tons
	POWER, main coils 500, pole tips 10
ACCELERATOR STAFF, OPERATION and DEVELOPMENT	total 510 kW; cooled by H ₂ 0
	YOKE/POLE area 210 %; θ sec (Sect Mag) deg
SCIENTISTS ENGINEERS	TOTAL POWER, installed 2.2 MW normal load 1.0 MW
TECHNICIANS CRAFTS	normal load 1.0 MW
ADMIN & CLERTOTAL	arc type with
GRAD. STUDENTS involved during year	ION SOURCE, int heated cathode
OPERATED BY Res staff or Sp operators	ext
BUDGET, op & dev	
FUNDED BY	ACCELERATION SYSTEM
RESEARCH STAFF, not included above	DEES, number 2 , width 180 deg
	BEAM APERTURE 4-14 cm; DC BIAS 0 kV
USER GROUPS, in house outside	TUNED by, coarse MS , fine
STAFF SCIENTISTS, in house outside	RF 3 to 6 MHz, stable ± 100 /10 ⁶
TOTAL RES STAFF, in house outside	Orb F 1.5 to 5.6 Mc/s; GAIN 600 kV/t
GRAD STUDENTS involved during year	HARMONICS, RF/OF, used
RES. BUDGET, in house	DEE-Gnd, max <u>150</u> kV, x/field, min cm,
FUNDED BY	STABILITY, (pk-pk noise)/(pk RF volt)
	RF PHASE stable to \pm deg RF POWER input, max 250 kW
FACILITIES FOR RESEARCH PROGRAMS	RF POWER input, maxkW
1500	RF PROTECT curcuit, speed µs
SHIELDED AREA, fixed 1500 m ²	type
movablem² TARGET STATIONS 10 in 7 ROOMS	EXTRACT System dc electrostatic with
STATIONS SERVED AT THE SAME TIME, max 1	magnetic channel
	SELECTED REFERENCES
MAG SPECTROGRAPH, typeON-LINE COMPUTER, model	
FACILITIES for:	Nucl. Instr. Meth. 93, 3, 557
	(1971)
Isotope production	
	*as per cablegram 5/14/75
Biological Time-of-Flight Study	**Being converted to U-400, K = 625
	First operation expected 1979.
On-Line Mass Separation	rital operation expected 1979.

ENTRY NO. 93 (cont.) CHARACTERISTIC BEAMS

BEAM PROPERTIES

0						
				Me	asured	Conditions
		Goal	Achieved			
	Particle	(MeV)	(MeV)	Pulse Width	RF deg	_ μA of MeV
ENERGY	12 C 2+ 22 Ne ⁴⁺ 40 Ar ⁷⁺	(μA)	83 182 305 (_(AA)	Res, ΔΕ/Ε 0.4-0.5	<u>1</u> %	_ μA of 182 MeV Ne ⁴⁺ _ μA of MeV Ne ⁴⁺ _ μA of MeV MeV _ μA of 83 MeV
Internal	11 B ²⁺		200 200	VACUUM norm 2	MPDOWN time 10 hr	
External	22 Ne 4+ 31 D6+		50 15	OPERATING PROGR	IAMS, time dis	t
	40 A 72 7+		- ' 2	Basic Nuclear Phys	sics	%
	<u> AL</u>			Solid State Physics	s	%
		(part/s)	(part/s)	Bio-Medical Applie	cations	%
				Isotope Production	n	%
Secondary	¹³⁶ Xe ⁹⁺		3.1012			%
HEAVIEST ion	184 W 12+		10"			

OTHER FEATURES and OPERATION SUMMARY