NAME OF MACHINE OR SAY 200 MeV Sy INSTITUTION Institut de Physique Nuc	nchrocyclotron DATE 1978
ADDRESS 91400 Orsay B.P. n°. 1	lealife
IN CHARGE H. Langevin - A. Laisné	REPORTED by P. Debray
HISTORY AND STATUS	MAGNET
DESIGN, date 1972 MODEL tests 72-73  ENG. DESIGN, date 1973  CONSTRUCTION, date Sept. 1975  FIRST BEAM date (or goal) 20-6-1977  MAJOR ALTERATIONS  OPERATION, 48 hr/wk; On Target hr/wk  TIME DIST., in house %, outside 100 %  USERS' SCHEDULING CYCLE weeks  COST, ACCELERATOR env. 10 MF  COST, FACILITY, total env. 20 MF  FUNDED BY Institut National de Physique  Nucléaire et de Physique des Particules (IN2P3)  ACCELERATOR STAFF, OPERATION and DEVELOPMENT  SCIENTISTS ENGINEERS 2  TECHNICIANS 6 CRAFTS 5  GRAD STUDENTS involved during year  OPERATED BY Res staff or 6 Operators	POLE FACE diameter $320$ cm; R extraction $140$ cm GAP, min $30$ cm; Field $40$ kG max $40$ cm; Field $16$ l 5kG AVERAGE FIELD at R ext $14$ 8 kG ampere turns CURRENT STABILITY $+20$ parts/ $10^6$ ; Bmax/(B) MUMBER OF SECTORS ; SPIRAL, max deg POLE FACE COIL PAIRS: AVF $1$ /sec; Harmonic correction Rad grad /sec or Circ coils 1 weight: Fe tons; Coils tons CONDUCTOR, Material and type Cu STORED ENERGY MJ COOLING SYSTEM De-ionized water POWER: Main coils $350$ max, kW YOKE/POLE AREA $100$ % SECTOR ANGLE (Sep Sec) deg ION ENERGY (Bending limit) E/A = $223$ q $^2/A^2$ MeV
BUDGET, op & dev FUNDED BY IN2 P3	(Focusing limit) E/A = 223. q/A MeV  ACCELERATION SYSTEM
RESEARCH STAFF, not included above  USERS, in house outside  GRAD STUDENTS involved during year	HARMONICS, RF/Orb F, used 3.  DEE-Gnd, max 20 kV, min gap 0.4 cm  STABILITY, (pk-pk noise)/(pk RF volt)  RF PHASE stable to ± deg  RF POWER input, max 100 kW  RF PROTECT circuit, speed 5 µsec  Type Blocking of the Amplitude Modulat  FREQUENCY MODULATION, rate 430; 700-1100sec  MODULATOR, type Rotating condenser  BEAM PULSE, width  VACUUM SYSTEM  PUMPS, No., Type, Size 1 diff. pump (16000 l.s)
REFERENCES/NOTES	OPERATING PRESSURE 1-5 µTorr,  PUMPDOWN TIME 40 hrs  ION SOURCES/INJECTION SYSTEM Pulsed Livingtone cathode  EXTRACTION SYSTEM Regenerative Extraction E.M. and M.S. channels.  CONTROL SYSTEM

## ENTRY NO. FM-5 (cont.)

## **CHARACTERISTIC BEAMS BEAM PROPERTIES** Measured Conditions Goal Achieved Particle (MeV) (MeV) Pulse Width \_\_\_\_RF deg \_\_\_\_μA of \_\_\_\_MeV \_\_ Phase Exc, max \_\_\_\_\_RF deg \_\_\_\_\_µA of \_\_\_\_\_MeV \_\_\_\_\_ **ENERGY** Р 200 and 170 Extract Eff 70 % \_\_\_\_\_μA of \_\_\_\_\_ MeV \_\_\_\_\_ d 108 and 90 Res, $\Delta E/E$ \_\_\_\_\_% \_\_\_\_\_μA of \_\_\_\_\_ MeV \_\_\_\_\_ 3He<sup>+</sup> 283 and 238 Emittance 220 and 182 CURRENT $\text{(mm-mrad)} \left\{ \frac{8.71 \text{ axial}}{2.0.71 \text{ radial}} \right\} = \frac{0.5 \, \mu\text{A of } 200 \text{ MeV} = P}{200.00 \, \mu\text{A}} = \frac{10.00 \, \mu\text{A}}{200.00 \, \mu\text{A}} = \frac{10.00$ $(\mu A)$ (µA) Internal 10 3 **OPERATING PROGRAMS, time dist** 3He<sup>+</sup> Basic Nuclear Physics External 7\_ Solid State Physics Bio-Medical Applications Isotope Production 30 (part/s) (part/s) Development \_\_\_ 10 Secondary

PLAN VIEW OF FACILITY, NOTEWORTHY FEATURES, OPERATION SUMMARY, ADDITIONAL REFERENCES

