NAME OF MACHINE Goettingen Synchro	ocyclotron DATE 8/1/78 Lingen, II. Physikalisches Institut
INSTITUTION <u>Universitaet of Goett</u>	ingen, II. Physikalisches Institut
ADDRESS Bunsenstr. /-9, 3400 Go	pettingen/BRD
IN CHARGE WD. Schmidt-Ott	REPORTED by
	MACNITY
HISTORY AND STATUS	MAGNET 190 75
DESIGN, date 1958 MODEL tests	POLE FACE diameter 180 cm; Rextraction 75 cm
ENG. DESIGN, date	GAP, min35
CONSTRUCTION, date 1960-1962	max cm; Field kG }
FIRST BEAM date (or goal) int. beam 1962 MAJOR ALTERATIONS ext. beam 1962	AVERAGE FIELD at R ext 14.2 kG ampere turns
MAJOR ALTERATIONS EXT. Deam 1962	
	NUMBER OF SECTORS ; SPIRAL, maxdeg
OPERATION, 50 hr/wk; On Target 40 hr/wk	
TIME DIST., in house 90 %, outside 10 %	Harmonic correction
	Rad grad/sec or Circ coils
COST, ACCELERATORDM $4.2 \times 10^6$	WEIGHT: Fe 250 tons; Coils 2 tons CONDUCTOR, Material and type Aluminium
COST, FACILITY, total DM $5.9 \times 10^{\circ}$	CONDUCTOR, Material and type Aluminity unit
FUNDED BY <u>Fed. Rep. of Germany</u>	
Building: Land of Niedersachsen	COOLING SYSTEM Demineralized water
ACCELERATOR STAFF, OPERATION and DEVELOPMENT	
scientists 1 engineers 1	Trimming coilsmax, kW
scientists 1 engineers 1 TECHNICIANS 2 CRAFTS	YOKE/POLE AREA 113 %
GRAD STUDENTS involved during year	SECTOR ANGLE (Sep Sec)deg
OPERATED BY Res staff or 2 Operators	ION ENERGY (Bending limit) $E/A = 13.9 \text{ q}^2/\text{A}^2 \text{ MeV}$
BUDGET, op & dev	(Focusing limit) E/A =q/A MeV
FUNDED BY Land of Niedersachsen	ACCELERATION SYSTEM
DESEADOU STAFE and included above	DEES, number 1 angle 180 deg
RESEARCH STAFF, not included above	REAM ARESTURE 4.0 am: DC RIAS F 10/
USERS, in house 20 outside 5	
GRAD STUDENTS involved during year 10	RF
RES. BUDGET, in house	Orb F Sameto mHz; GAIN, max13 kV/turn
FUNDED BY Land of Niedersachsen	HARMONICS, RF/Orb F, used 1  DEE-Gnd, max 20 kV, min gap fixed 7 cm
Fed. Rep. of Germany	DEE-Gnd, max 20 kV, min gap 1 XeQ /cm
FACILITIES FOR RESEARCH	STABILITY, (pk-pk noise)/(pk RF volt)
SHIELDED AREA, fixed 160 m <sup>2</sup>	RF PHASE stable to ±
movable m <sup>2</sup>	THE TOWER MAY
movable m <sup>2</sup> TARGET STATIONS 5 in 2 rooms	RF PROTECT circuit, speed
STATIONS served at same time, max1	
MAG SPECTROGRAPH, type	FREQUENCY MODULATION, rate 2000 /sec MODULATOR, type rotating capacitor
COMPUTER, model LSI 11/03	BEAM PULSE, width 25 µsec
OTHER FACILITIES Gas-Transport-System	BEAM POLSE, Width
Facilities for Short-Lived	VACUUM SYSTEM
Spectroscopy and Chemical Separa	A-PUMPS, No., Type, Size Diff. pumps 6000 1/sec,
tions	modulator: 1000 l/sec
	OPERATING PRESSURE 2 μTorr,
REFERENCES/NOTES Cyclotron:	PUMPDOWN TIME 5 hrs
W. de Groot: Philips Techn. Rev.	
Vol 12, No 3 (1950)	ION SOURCES/INJECTION SYSTEM internal gas discharge (arc)
G.T. de Kruiff, N.F. Vester: CERN	- Zincornar yas arsonarye (arc)
Report 63-19,80 (1963)	
Other Facilities; N. Instr. Meth.	modified regenerative extr. with magr
<u>130</u> , 177 (75); 141, 553 (77)	control system
· · · · · · · · · · · · · · · · · · ·	conventional

## ENTRY NO. FM-6 (cont.)

IC BEAMS			BEAM PROPERTIES	
	Goal	Achieved	Measured Condit	tions
Particle	(Me∨)	(Me∨)	Pulse WidthRF degµA of	MeV
đ	27	27.7		MeV
54	54	55.4	Extract Eff 5 %µA of	MeV
			Res, $\Delta E/E$ $\mu A$ of $\mu A$	MeV
d	10 0.2	(μA) 15 1.3	( <u>I U U</u> radial )	MeV
2 cm <sup>2</sup> :d		0.1	Basic Nuclear Physics Solid State Physics Bio-Medical Applications	70 <sub>%</sub>
	(part/s)	(part/s)	Isotope Production  Development	25 % ———————————————————————————————————
	d 	Goal (MeV)  d 27  54  d 10  0.2  2 cm²:d	Particle (MeV) (MeV) $\frac{d}{d}$ 27 27.7 $\frac{54}{3}$ 55.4 $\frac{d}{10}$ 15 $\frac{(\mu A)}{0.2}$ 1.3 $\frac{2 \text{ cm}^2 : d}{3}$ 0.1	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$

PLAN VIEW OF FACILITY, NOTEWORTHY FEATURES, OPERATION SUMMARY, ADDITIONAL REFERENCES