


The FAIR Accelerator Facility



goals:


higher intensity (low charge states)

higher energy (high charge states)

production of antiprotons


high quality secondary beams (cooling)

The FAIR 13 Tm Storage Rings




Antiproton Target and Separator


production rate of antiprotons





temperature of target



target station
shielding and handling




Antiproton Separator



according to tracking calculations about 70 % of the produced antiprotons will be stored in the CR

The Collector Ring CR





circumference 216 m
magnetic bending power 13 Tm
large acceptance $\epsilon_{x,y} = 240$ (200) mm mrad
 $\Delta p/p = \pm 3.0$ (1.5) %

**fast stochastic cooling (1-2 GHz)
of antiprotons (10 s) and
rare isotope beams (1.5 s)**

*fast bunch rotation at $h=1$
with rf voltage 200 kV
adiabatic debunching*

*optimized ring lattice (slip factor)
for proper mixing
large acceptance magnet system*



**additional feature:
isochronous mass measurements
of rare isotope beams**

 $\eta = 0$

Fast Bunch Rotation in CR

**Fast bunch rotation of SIS100 bunch
to provide optimum initial parameters
for stochastic cooling
total rf voltage 200 kV at $h=1$ reduces
the momentum spread ($2.5 \rightarrow 0.5$ %)
after passage of production target**

SIS100 bunch after target



**bunch rotation cavity
(SIS18 bunch compressor)**

voltage 40 kV


length 1 m

frequency range 1.18 – 1.38 MHz



rotation time ~ 100 μ s

Stochastic Cooling Developments


vacuum tank
with actuators for electrode movement
including cold heads (20 K) and cooled
pre-amplifiers



for details: **THPP051**




prototype electrode
($\beta = 0.83-0.97$)



voltage and phase flatness

CR Closed orbit correction




CR Closed orbit correction

MAD and WINAGILE simulations

Distribution of initial vert. abs. max. orbit excursions

Total no. of orbits in sample 100
 No. of correction failures 0
 Abs. max. initial excursion [m] 0.051265
 Abs. av. initial excursion [m] 0.023751
 Abs. RMS initial excursion [m] 0.009816



Distribution of final vert. abs. max. orbit excursions

Abs. max. final excursion [m] 0.002722
 Abs. av. final excursion [m] 0.001632
 Abs. RMS final excursion [m] 0.000432



Before correction

The most probable COD ≈ 20 mm

After correction

The most probable COD ≈ 1 mm

Alignment rms errors used in tracking studies

Element	Δx [mm]	Δy [mm]	Δz [mm]	Roll [mrad]
Dipole	0.2	0.2	0.5	0.5
Quadrupole	0.2	0.2	0.3	0.5
Sextupole	0.2	0.2	0.3	0.5

Closed orbit excursions before correction

	PBAR		RIB		ISO	
	hor	ver	Hor	ver	hor	ver
$\Delta X_{\max}$ [mm]	17.22	20.93	42.17	51.06	17.07	15.19
$\Delta X_{\text{average}}$ [mm]	9.76	11.57	14.71	23.75	10.71	8.64

Closed orbit excursions after correction


	PBAR		RIB		ISO	
	hor	ver	hor	ver	hor	ver
$\Delta X_{\max}$ [mm]	3.07	2.52	1.40	2.64	0.45	0.92
$\Delta X_{\text{average}}$ [mm]	1.10	1.20	0.81	1.34	0.25	0.46

Orbit corrections are important for optimum stochastic cooling



RESR

The Antiproton Accumulator Ring



circumference	240 m
magnetic bending power	13 Tm
tunes Q_x/Q_y	3.12/4.11
momentum acceptance	± 1.0 %
transverse accept. h/v	25×10^{-6} m
transition energy	3.3-6.4

accumulation of antiprotons by a combination of rf stochastic cooling

max. accumulation rate $3.5 (7) \times 10^{10}/h$
max. stack intensity $\sim 1 \times 10^{11}$

***additional mode:
fast deceleration of RIBs to
a minimum energy of 100 MeV/u
for injection into NESR
(collider mode)***




Dynamic Aperture Calculations

$Q_x = 3.11, Q_y = 4.12$


field
errors

Harmonic order	2	3	4	5	6	7	8	9	10
Dipole	0	0.12	0	-0.016	0.0	0.017	0	-0.001	0
Quadrupole	0	4.0	2.8	3.0	14.0	1.8	2.5	1.0	2.0
Sextupole	0	0	0	0	0	0	0	6.0	0





$\Delta p/p = 0$



$\Delta p/p = -1 \%$




$\Delta p/p = +1 \%$



Frequency Map Analysis *calculated with PTC code (MAD)* for details: **THPC011** **THPC057**

Antiproton Accumulation in RESR




electrodes of
Faltin type


core cooling 2-4 GHz
longitudinal
horizontal
vertical

tail cooling 1-2 GHz
longitudinal

injection of 1×10^8 antiprotons every 10 s
pre-cooling in CR provides
 $\delta p/p = 1 \times 10^{-3}$, $\varepsilon_{x,y} = 5$ mm mrad
maximum stack intensity: 1×10^{11} antiprotons
pre-cooling after injection considered as option




The New Experimental Storage Ring



Circumference [m]	222.8
Straight section length [m]	18
Horizontal acceptance [mm mrad]	150
Vertical acceptance [mm mrad]	40
Momentum acceptance [%]	± 1.5
Max. momentum deviation [%]	± 2.5
Horizontal tune	4.2
Vertical tune	1.87
Transition energy	4.59
Maximum dispersion [m]	6.8
Horizontal chromaticity	5.9


Accelerator Issues at NESR



- Electron cooling of ions and antiprotons
- Deceleration of ions to 4 MeV/u (in 1.6 s) and antiprotons to 30 MeV
- Fast extraction (1 turn)
- Slow (resonance) extraction
- Ultraslow (charge changing) extraction
- Longitudinal accumulation of RIBs
- Electron-Ion collisions (bypass mode)
- Antiproton-ion collisions
- Internal target
- Electron target
- High precision mass measurements

NESR Electron Cooler

design by BINP, Novosibirsk



Cooler Parameters



energy	2 - 450 keV
max. current	2 A
beam radius	2.5-14 mm
magnetic field	
gun	up to 0.4 T
cool. sect.	up to 0.2 T
straightness	2×10^{-5}
vacuum	$\leq 10^{-11}$ mbar

- Issues:**
- high voltage up to 500 kV
 - fast ramping, up to 250 kV/s
 - magnetic field quality

Electron Cooling in the NESR





$^{132}\text{Sn}^{50+}$, $N_i = 10^8$, $E = 740 \text{ MeV/u}$,
 $I_e = 1 \text{ A}$, $r_e = 0.5 \text{ cm}$, $B = 0.2 \text{ T}$



emittance

momentum spread

Antiprotons, $E_i = 800 \text{ MeV}$
 $I_e = 2 \text{ A}$, $r_e = 1 \text{ cm}$, $B = 0.2 \text{ T}$




BETACOOOL simulations Parkhomchuk model

Accumulation of RIBs in NESR

basic idea: confine stored beam to a fraction of the circumference, inject into gap
apply strong electron cooling to merge the two beam components

⇒ fast increase of intensity (for low intensity RIBs)



$^{132}\text{Sn}^{50+}$


$E_k = 740 \text{ MeV/u}$

Longitudinal stacking
with Barrier Buckets
(simulation by T. Katayama)


Proof of Principle in the ESR




moving barrier



fixed barrier




$h=1$ unstable fixed point



all three schemes worked well:
cooling times close to expectations
efficient accumulation

high quality timing and kicker pulses required
Intensity limits: rf voltage and instabilities




for details:

THPP048




Civil Construction of CR/RESR

Building




Ring Tunnel




NESR Civil Construction Planning

Lower (ring) level



rf, diagnostics, vacuum, controls

Upper level



power converters, common systems

FAIR Storage Ring Concept

FAIR Technical Division - Storage Ring:

C. Dimopoulou, A. Dolinskii, O. Gorda, V. Gostishchev,

K. Knie, I. Nesmiyan, F. Nolden, D. Obradors-Campos, C. Peschke

many contributions from technical experts of GSI Accelerator and FAIR Division

advice by B. Franzke, T. Katayama,

D. Möhl, L. Thorndahl (CERN)

contributions by P. Shatunov, D. Shvartz and others from BINP