


Precision Large Scale Synchronization System at the European XFEL



Cezary Sydlo
on behalf of the Lbsync Team



MSK / DESY


Grand Rapids, Michigan, 22th August 2017



Outline

- European XFEL Location and Synchronization Overview
- Optical Reference Distribution
 - Master Laser Oscillator
 - Fiber link stabilization
- Endstations
 - Laser-to-RF: Control RF phase
 - Laser-to-Laser: Control Laser timing
 - Bunch Arrival Monitor: Measure bunch arrival time
- Summary


The European XFEL and DESY in Hamburg, Germany



Why is the synchronization optical

- Ideal for all-optical slave laser locking e.g. pump-probe-laser etc.
- High resolution elektron bunch arrival time measurement available
- High precision laser-to-RF phase comparator available
- Low loss in single mode fibers for long distances $\sim 0.3\text{dB} / \text{km}$
- Low loss in polarization maintaining fibers $\sim 0.8\text{dB} / \text{km}$
 - 21 km installed at European XFEL, about 6 km at FLASH
 - Quite expensive but ...
 - No timing error due polarization mode dispersion
 - No polarization correction necessary

System Overview



Installation Overview

Master-Synchronization Room

Two Master-Laser-Oscillators

- For redundancy


Up to 24 Link-Stabilization-Units

Sub-Synchronization Hutch

Synchronized from Master


- By two Links for redundancy

Up to 20 Link-Stabilization-Units



Optical Reference Distribution


Master-Laser-Oscillator



■ Origami 15 from OneFive



- Compromise between timing resolution and optical bandwidth
- High repetition rate of 216.667 MHz (1.3GHz / 6)
- Locked to the Master-Oscillator (1.3GHz with GPS frequency standard)
- **Low phase noise, low amplitude noise**

Master-Laser-Oscillator: Overview




Courtesy: M. Heuer
(Controls & FW)

Master-Laser-Oscillator: Locking



- Locking with a Photodiode
 - Low amplitude noise required
 - MLO: Origami 15 ✓
 - Calibrate for AM-PM effect!
- IQ detection in FW => phase shifter
 - Convenient for installation phase
- **Amplitude insensitive set-up**
like **Laser-to-RF** in preparation

Master-Laser-Oscillator: Phasenoise



Integrated Phasenoise

1KHz – 1MHz

► MO: 5.1fs, MLO: 4.1fs

100Hz – 1MHz

► MO: 7.4fs, MLO: 9.6fs


Next steps

Replace MO power-amp

► *DONE on 16.8.*

Improve MLO lock


Link-Stabilization-Units: Principle



Courtesy: M. Heuer
(Controls & FW)


- Installed fibers influenced by temperature, humidity, vibration
- The balanced optical cross-correlator (OXC) detects timing changes
- The pulse propagation time through the stabilized path is held constant by a fiber stretcher and a motorized optical delay line.
- A lot of custom optomechanics
- **Learned a lot from operation at FLASH!**

Link-Stabilization-Units: Out-of-loop measurement



- Prototype tested under **realistic** for meaningful results
 - Partly uncompensated fibers at link end exposed to air flow, vibration, etc
 - **Worst case estimation** for operation of endstations in rack installations


Link-Stabilization-Units: Installation in MasterSyncRoom



Optical table
(SuperInvar)

- Reference distribution
 - MLO in operation
 - 13/18 Links in operation (max. 44)
 - 21 km of PMF installed
- Preliminary Results
 - Slope around 5mV/fs ✓
 - Noise 0.1mV RMS 1MHz ✓
 - In-loop jitter < 0.2 fs RMS ✓
 - Observe up to 200 ps/km drift compensation

MTCA based control electronics: Infrastructure footprint



■ VME based system at FLASH

■ 4x 42HE racks


■ 2 MLOs + 16 Links

■ MTCA based system at XFEL

■ 1x 42HE racks


■ 2 MLOs, up to 32 Links

MTCA based controls: Concept



- Fiber link controls challenging
 - Low piezo resonance frequency of about 18kHz
 - Long response time possible of up to 40 us
- Solution
 - 6th order state space controller
 - Can be also useful for lasers
 - Include Smith predictor

MTCA based controls: Results





- Example: Coarse tuning step (observed up to 10x / h @ XFEL)
 - When piezo fiber stretcher reaches limits a motorized delay line drives
- LQG implementation in 6th order state-space controller outperforms conventional PID control


Endstations

Laser-to-RF: Reference Module Optical (RefmOpt)

- Optical Re-Synchronization of the 1.3GHz for LLRF
 - LLRF cable drift compensation
 - High Resolution
 - Expected Drift < 3fs / 48h
 - 8/9 Units installed (max. 10)




Laser-to-RF: Short term performance at XFEL



REFMOPT.A3M.247.L2



- Detector noise < 2fs (up to 125kHz)
- 11 fs out-of-loop jitter (MO vs. MLO):
 - MLO-to-MO lock (has poor MO power amp)
 - 250m unstabilized RF cable
 - 260m PM fiber link
 - Phase comparator in tunnel
- 9.6 fs in-loop jitter
- Up to now low bandwidths used
- Need new measurements due to **replaced MO power amp**

Laser-to-RF: Long term performance at XFEL




- A3 (247m), A4 (295m) and A8 (611) compensate 15ps of RF cable drift !
- All stations are in the main linac tunnel, but experience similar drift
- Drift dominated by (common) media shaft

Laser-to-Laser




- Synchronization of external Laser systems
 - Injector laser, Pump-probe laser,...
 - Engineered set-up
 - ▶ “One size fits all”
 - ▶ Simplified mainainance
 - Balanced cross correlation
 - Sensitivity up to 20mV / fs
 - Out-of-loop jitter < 10fs RMS
 - 2 / 6 installed


Bunch Arrival Monitor from “Special Diagnostics”




- Bunch Arrival Time Measurement
- 6/7 Units installed (max. 8)
- Forseen for arrival time feedback




Pickup (40GHz)




Body



Beamline Installation




BAM Front-End



Rack Installation


Bunch Arrival Monitor: Resolution




Charge (pC)	Sensitivity (fs/%)	Resolution (fs)
50	120	24.0
100	84	16.8
140	67	13.4
200	38	7.6
450	27.8	5.6

- Resolution not optimum yet
 - Amplitude noise too high (x2)
 - Electronic noise
 - ▶ Filters underway
 - Electromagnetic Interference
 - ▶ Needs improvement
 - Signal too low (x1.5 – x2)
 - ▶ Changed Rack placing
 - ▶ Cable about 3dB/m @ 40GHz

Bunch Arrival Monitor: Overview



Bunch Arrival Monitor: Results



Expected compressions confirmed


BC0: 2, BC1: 8-10, final arrival time jitter is 20 fs RMS **without feedback**

Helped already to track down a source of instabilities

Summary

- Optical Synchronization in operation and ready for future expansion
- Still issues come up, get identified and solved
- Sub 10 fs for the synchronization already achieved
- First user experiments in 4 weeks!
- More to come ...

Thank you on behalf of (core) LbSync group (MSK/DESY)



Please visit also the tutorial:
“Integrated Photonics to the rescue of Femtosecond Beam Diagnostics”
by **Franz Kärnter (CFEL)** at 11am