

SNS Commissioning and Upgrade Plans

Isidoro E. Campisi

For the SNS Team

SRF 2007, Beijing, China


October 15, 2007



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY

Spallation Neutron Source


- The SNS is a short-pulse (700 ns) neutron source, driven by a 1.4 MW proton accelerator, becoming the world leading neutron scattering facility
- Construction project was a collaboration of six US DOE labs



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



SNS Accelerator



- Superconducting linac has 33 medium β cavities and 48 high β cavities.
- Designed for 2.1 K. Until recently ran at 4.5 K (lower repetition rates to decrease HV converted modulator failures and decrease load on cryogenic plant).
- Pulsed Superconducting RF operated at 805 MHz, 1.3 ms, 7.8% RF duty cycle



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
 SRF 2007, Beijing, China, October 15, 2007



Status at the Cornell SRF Workshop, July 2005


- Completed installation of all 23 cryomodules
- Completed installation of all 32 warm sections
- Completed testing at 4.5 K of all cavities at 10 Hz
- Preparing for beam commissioning in August 2005



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



SCL installation



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Major milestones since July 2005


- August 2005: beam commissioning of Superconducting Linac at 550 MeV straight ahead (7.5 kW dump)
- February 2006: Ring Commissioning with full injection energy from the linac (above 850 MeV)
- 28 April 2006: Beam on Target
- July 2006: Official start of Operations
- Goal of reaching full SNS design capability at the end of a three-year ramp-up period, which started October 1, 2006
 - 1.4 MW beam power
 - 5000 hours of operation per year
 - >90% availability (hours of neutron production delivered/hours scheduled)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007




Performance Goals: Power, Hours and Reliability



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



SNS power ramp up schedule




Since June 2007 we have been running at 30 Hz 2.1 K.
From November 1st on, always at 60 Hz (Target lifetime)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Power Ramp-up Progress in the Past Year




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Presently SNS is the most powerful Spallation Source

180 kW run

Accumulated
beam power
(daily/monthly)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October15, 2007



Some SNS Linac Beam Performance Measures *(through the entire linac)*

	Design	Highest Ever (Individual)	Highest Beam Power (Simultaneous)
Energy (GeV)	1.0	1.01	0.88
Rep Rate (Hz)	60	60	30
Pulse Length (mSec)	1	1	0.55
Beam Current * (mA)	26	20	13
Beam Power (MW)	1.5	0.18	0.18

* Time average including ~ 30% chopping



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Superconducting Linac


- Designed and built by Jefferson Laboratory
- SCL accelerates beam from 186 to 1000 MeV
 - Reached 1011 MeV
 - Run at 890 MeV most of the time
- 81 Niobium cavities in 23 cryomodules (33 medium .61 beta, 48 high .81 beta)
- Cavities are now operated at 2.1 K
- Until Spring 2007 mostly run at 4.5 K (can run up to 30 Hz, 1.3 msec RF pulse width)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007




SNS Cryomodule and SRF cavity layouts




HOM Couplers

- HOM couplers added as extra safety against longitudinal instabilities
- Some HOM feed-throughs have been damaged or show abnormal transmission curves
- Exact cause of anomalies not completely known, but conservatively turned off or run at limited gradients




- Some cavities are limited by coupling of fundamental power via HOM filters (one is off, one is being repaired by blanking the HOM ports)


HOM Couplers behavior



1~5 Hz




10 Hz





30 Hz

Ex. 15a Eacc=15.4 MV/m



Sharp electron loading appeared
after ~20 min operation at 30 Hz
accompanied by vacuum excursions

FPC Vacuum interlocks





OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007




Window vacuum interlock

Very difficult turning on cavities during the first year of operation



Difficult to find a proper coupler cooling rate



Will switch to current monitor for window interlocks




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY

SRF 2007, Beijing, China, October 15, 2007



Radiation patterns

Pulsed Field Emission Radiation




Microseconds/10

Radiation correlated with cavity fields (most cavities)

Traces are fast and filtered detector responses

Radiation correlated with traveling waves in the coupler (about 10 cavities)







Microseconds/10



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Cavity-coupler interaction




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY

SRF 2007, Beijing, China, October 15, 2007





Field Emission Heating Across Cavities

b cavity phase → a cavity beam pipe





a cavity phase → a cavity beam pipe



Lorentz force detuning

Dynamic detuning as expected ($K_{LFD} \rightarrow 3-4$:medium; 1-2:high)

Some cavities show resonance phenomena at higher repetition rates



The 2 kHz components shows resonances at higher repetition rate in some of medium beta cavities.




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007




SCL Subsystems– Piezo Tuner

- Piezo tuners installed compensate for the Lorentz detuning
- Not yet used in operations
- If piezo stack fails, the cavity cannot be operated (real event in February 2007)
- May be activated on selected cavities if necessary





Accelerating gradients and statistics



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Accelerating gradients distributions




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Field emission threshold

Maximum fields and FE threshold



Average maximum gradient (31 MB and 44 HB): 17.6 MV/m

Average FE threshold: 10.0 MV/m


Operating gradients are kept somewhere between the FE threshold and 90% of the maximum value



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007





Dynamic heat load at 2.1 K



Heater compensation at 2.1 K for all operating cavities.
A few cavities, operated into heavy field emission, contributed almost half of the dynamic load.
At 4.5 K the field emission loading is negligible compared to the BCS losses.

Cryogenic loads at 2.1 K



Set 1; Below FE threshold (~9MV/m)

Set 2; 80 % of individual limits

Set 3; 88 % of collective limits

Avg(set2)-Avg(set3)~1MV/m

Total dynamic heat loads due to different sources




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



RF control stability for SCL

Normalized Amplitude control



The RF Control System provides excellent amplitudes and phase stability for all operating cavities

Next week LLRF Workshop in Knoxville




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Energy gain: SCL Phase Scan using BPMs

BPM phase diff




Cavity phase

SCL phase scan for first cavity

Solid = measured BPM phase diff

Dot = simulated BPM phase diff

Red = cosine fit



- Relies on absolute BPM calibration




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007




Drifting Beam Method to Determine Cavity Phase and Amplitude Setpoints

proton beam 422MeV, 15mA, 40us

signals measured with/without
cavity detuning



simulations from the model with
superimposed measured noise



- Drifting beam excites the cavity fields.
- Comparison to model allows calibration of the phase and amplitude
- Phase prediction ~ 1 degree, amplitude ~ 4% compared to phase scan technique



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October15, 2007



Operations constraints


- **Drastically improved trip rates by better understanding of:**
 - underlying physical phenomena (outgassing, arcs, discharges, radiation, field emission, beam strike, dark current etc.)
 - components response (arc detectors, HOM couplers, Cold cathode gauges, Coupler cooling, end group heating)
 - controls (LLRF logic, programming, choice of limits and stability parameters)
- **Continue to improve performance and ultimate beam power by:**
 - Optimizing gradients, modulator voltages, matching of klystrons to cavities, circulator settings, available forward power for beam loading etc.



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



SCL Tune-up – Linac Energy Gain




- Energy gain per cavity is predictable to a few 100 keV and distributed about 0.
- Final energy is predictable to within a few MeV
- This leads to shorter and shorter setup times and rapid fault recovery, even for many “missing cavities” (operational availability)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October15, 2007



Cavity Fault Recovery Application




- In the spring 2006, 11 cavities had to be either turned off or have their amplitudes reduced for safe operation, 1 cavity was returned to operation
- The fault recovery scheme was applied “all at once”
- Phase scan spot checks indicate the scaling was within 4 degrees
- No detectable change in beam loss



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Beam Loss / Activation



- Ultimately the beam loss and components' activation dictate the machine setup
- Components internal to Cryomodule become activated and planning for repairs becomes more complicated

SCL Summary


- Extensive studies of cavities, components and cryomodules have been performed
- 1 GeV demonstration at 15 Hz, 4.4 K (79 cavities) to linac dump
- 60 Hz demo at 860 MeV, 2.1 K (75 cavities) with beam to target
- Supporting beam power ramp up
- SCL is now providing stable/reliable acceleration for Neutron Production
- Repairs and spare acquisition plans being evaluated (Pressure Vessel Code requirements)



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



SRF Test Facility



Cryomodule Assembly

Chemistry

Assembly

Class



**Mezzanine
(lab space)**



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
 SRF 2007, Beijing, China, October 15, 2007



Rebuild (medium beta prototype)




OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Horizontal Test Apparatus

To be used for cavity qualification before string assembly, for tests of cavity/end group cooling and for High Peak Power Pulse Processing up to 5 MW, 1 ms.



Mechanical components ready for assembly



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Power (Energy) Upgrade Project

- Increase in beam power is achieved by a combination of beam current (26 to 42 mA) and beam energy (1.0 to 1.3 GeV) increase.
- All of the energy increase will be accomplished in the superconducting linac by:
 - Acquiring, installing and commissioning 9 additional high beta cryomodules, which include:
 - 36 high beta cavities
 - 36 fundamental power couplers
 - 36 Low level RF control systems
 - 36 high power klystrons (750 kW) and related RF components
 - 36 tuners
 - Modifications/improvements will be included into the CM

CD 1 approved the ENERGY increase

This part would be completed by 2013



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007



Summary

- SNS is now an fully operating facility providing proton beam for neutron production to users
- Achieved all of the design parameters separately
- Provides highest beam power of any spallation source
- Provides highest beam energy of any “proton” linac
- The SCL is gaining full operational experience on pulsed RF superconductivity
- Facilities are being put in place to make SNS a fully functional SRF Accelerator and Laboratory



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY
SRF 2007, Beijing, China, October 15, 2007

