



MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

MSU Re-accelerator

The Reacceleration of Low Energy RIBs at the NSCL

Xiaoyu Wu

National Superconducting Cyclotron Laboratory (NSCL)

Michigan State University (MSU)

East Lansing, MI 48824, USA

13th International Workshop on RF Superconductivity
October 15, 2006, Peking University, Beijing, China

Outline

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- **Low-Energy Rare Isotope Beams (RIBs) production**
- **Planned Low-Energy RIBs Facility at NSCL**
- **Re-accelerator**
 - **Design considerations**
 - **Accelerator system**
 - **Beam dynamics**
 - **Current status and future plan**
- **Summary**

Low-Energy RIB Production


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- **Strong demand from nuclear science for high quality low-energy RIBs for:**
 - **Precision mass measurements & Laser spectroscopy**
 - **Precision decay studies & Low energy coulomb excitations**
 - **Transfer reaction studies of astrophysical reactions**
- **Two RIB production methods**
 - **Isotope Separation On-Line (ISOL)**
 - **Produced at ~ rest**
 - **REX-ISOLDE & TRIUMF**
 - **Projectile Fragmentation**
 - **Produced at ~ 50 MeV/u**
 - **NSCL/MSU**

ISOL Facility Concept

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY


- High beam quality and low beam energy
- Limited to longer life time ($\tau > 1s$)
- Isotope extraction and ionization efficiency depend on chemical properties of element
- The most neutron-rich isotopes will have too low intensities and too short lifetimes to be suitable for re-acceleration




Projectile Fragmentation Facility Concept

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- Modest beam quality and high beam energy ($E/A > 50 \text{ MeV/u}$)
- Suitable for short-lived isotopes ($\tau > 10^{-6} \text{ s}$)
- Physical method of separation, no chemistry
- *Low-energy beams are difficult (emittance too large)*




Fast RIBs Production at the NSCL



- **In-flight particle fragmentation method**
 - Coupled cyclotrons produce high energy primary beams
 - Production target produce RIBs at velocity
 - A1900 Fragment Separator separate RIBs in-flight
 - Experiments performed with fast RIBs
 - Nuclear structure/Nuclear reactions

Low-Energy RIBs at the NSCL

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



- Prototype facility planned for stopping and re-accelerating RIBs produced and separated in-flight
- Important step toward a next-generation rare-isotope facility in the United States
- Three key steps:
 - Gas stopping
 - Charge breeding
 - **Re-acceleration**

Gas Stopping Method

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



- **Linear Gas Cell – works but has limitations**

- Intensity-dependent extraction efficiencies
- Extraction time of ~ 100 ms
- Low stopping efficiencies for light beams

- **“Cyclotron” Gas Stopper – under development**

- Shorter extraction times
- Higher beam rate capability




Georg Bollen/NSCL User Workshop 2007



NSCL Gas Stopping Plan

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



- Possibility of both stopping methods at the NSCL



Electron Beam Ion Trap (EBIT) Charge-Breeder

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- Charge breeder
 - $1+ \rightarrow N+$
 - More efficient acceleration
 - Electron gun/collector
 - Solenoid
 - Trap electrodes
 - 60 kV platform



MSU Reaccelerator Beam Specifications

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

Input Beam Parameters (<i>From EBIT</i>)	
Energy	12 keV/u
Q/A	0.2 – 0.4
Transverse Emittance (normalized)	0.6 π mm-mrad
Energy Spread	± 0.2 %
Output Beam Parameters (<i>On target</i>)	
Energy Variability	From 0.3 to 3.0 MeV/u
Bunch Width on Target	~ 1 ns
Energy Spread on Target	~ 1 keV/u
Beam Size on Target	~ 1 mm

MSU Reaccelerator and RIA/ISF




- **Design benefits from past RIA driver linac R&D efforts**
 - **Many similar components**
 - **Design experience**
 - **Beam simulation tools**
 - **SRF cavity and cryomodule prototyping**
- **Design and construction of the MSU reaccelerator will provide valuable experience for the future MSU Isotope Science Facility (ISF)**


MSU Reaccelerator Layout

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- Low Energy Beam Transport (LEBT)
- Radio Frequency Quadrupole (RFQ)
- Superconducting (SC) Linac
- High Energy Beam Transport (HEBT)



Low Energy Beam Transport



- **Transport, bunch and match RIBs into RFQ**


- 4 electrostatic quadrupoles
- 2 Superconducting solenoids
- Multi-harmonic buncher (MHB)
 - Three harmonics
 - High bunching efficiency: ~ 82%
 - Two $\lambda/4$ resonators

Low Energy Beam Transport




MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

Beam simulated
using RIAPMTQ

Beam envelopes
in the LEBT



Horizontal, vertical
and longitudinal
phase spaces at the
exit of the LEBT



Reaccelerator RFQ

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- **CW operation**
- **Room temperature structure**
- **Achieve small longitudinal emittance**
 - **$\sim 0.25 \pi$ keV/u-ns**
 - **External multi-harmonic buncher**
- **Enhanced acceleration efficiency**
 - **Shortened gentle bunching section**
- **Frequency: 80.5 MHz**
- **Length: 3.5 m**
- **Input energy: 12 keV/u**
- **Output energy: 600 keV/u**

RFQ Main Parameters


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

Charge to mass ratio, Q/A	0.2 – 0.4
Max. Intervane voltage (kV)	86.2
Peak electric field (MV/m)	16.7
Peak field ($E_{\text{kilpatrick}}$)	1.6
Number of cells	94
Synchronous phase (degree)	-20
Modulation factor	1.15→2.58
Average radius (mm)	7.3
Tip radius (mm)	6.0
Focusing strength	4.9


RFQ Beam Dynamics

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

The longitudinal acceptance ($\sim 0.8 \pi$ keV/u-ns) and beam phase space at the entrance of the RFQ



Horizontal, vertical and longitudinal phase spaces at the exit of the RFQ



$\varepsilon_z(90\%) = \sim 0.29 \pi$ keV/u-ns

Superconducting Linac

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



- **Acceleration or deceleration of the RIBs to the desired energy**
 - RFQ output energy: 600 keV/u
 - Final energy: 300 keV/u ~ 3 MeV/u
 - Maintain beam quality
- **SC linac advantages**
 - Requires very little rf power
 - High accelerating gradient for CW operation (100% duty factor)
 - Better operational flexibility and availability

Two SRF Cavity Types Used

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

$\beta_{\text{opt}}=0.041$


$\beta_{\text{opt}}=0.085$



Type	$\lambda/4$	$\lambda/4$
Optimum β	0.041	0.085
Frequency	80.5 MHz	80.5 MHz
E _{peak}	16.5 MV/m	20.0 MV/m
V _{acc}	0.46 MV	1.18 MV
E _{acc}	4.84 MV/m	5.62 MV/m
B _{peak}	28.2 mT	46.5 mT
Temperature	4.5 K	4.5 K
Length	0.095 m	0.21 m
Aperture	30 mm	30 mm

$\beta_{\text{opt}}=0.085$ Prototype Cavity

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



$\beta_{\text{opt}}=0.041$ Prototype Cavity

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY




SRF Cavity Prototype R&D


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- QWR $\beta_{\text{opt}}=0.085$
prototyped and tested
in 2003

- $Q_0: 5 \times 10^8$
- $E_p: 20 \text{ MV/m}$




- QWR $\beta_{\text{opt}}=0.041$
prototyped and tested
in 2007 – to be
presented at Tuesday
poster session



Transverse Focusing – Superconducting Solenoid


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY




- Symmetric focusing
- Allow more cavities per cryostat
- 2 dipole corrector coils for central orbit correction
- Peak magnetic field: 9T
- Adjacent to superconducting cavities
 - Active end bucking coils and niobium shield to minimize stray magnetic field
 - Obtain $\sim 10^{-6}$ reduction in B field

Superconducting Linac Cryomodules


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



- 1st Cryomodule
 - 2 Superconducting solenoids
 - 1 $\lambda/4$ SC cavity, $\beta_{\text{opt}}=0.041$
 - Transverse and longitudinal matching




- 2nd Cryomodule
 - 3 Superconducting solenoids
 - 6 $\lambda/4$ SC cavities, $\beta_{\text{opt}}=0.041$
 - Acceleration/deceleration: 1.2/0.3 MeV/u



- 3rd Cryomodule
 - 3 Superconducting solenoids
 - 8 $\lambda/4$ SC cavities, $\beta_{\text{opt}}=0.085$
 - Acceleration/rebunching

Superconducting Linac Prototype Cryomodules


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



- **Prototype cryomodule fabricated**
 - 80.5 MHz $\beta_{\text{opt}}=0.085$, $\lambda/4$ cavity
 - 322 MHz $\beta_{\text{opt}}=0.285$, $\lambda/2$ cavity
 - Superconducting solenoid
 - Superconducting quadrupole
- **Testing in progress**
 - Cavity performance
 - Magnet field effect on cavities
 - RF frequency stability, amplitude and phase controls
 - **Will compare with vertical test results**

SC Linac Prototype Cryomodules

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



(a) cold mass



(c) inner MLI



(e) outer MLI



(b) top plate



(d) 77 K shield




(f) vacuum vessel

Superconducting Linac Performance - [1]



MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- Beam simulations using IMPACT (~3 MeV/u)

Beam energy gains
along the SC linac



Beam transverse
envelopes and
longitudinal beta
function along the
SC linac




Superconducting Linac Performance - [2]


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- Adequate transverse and longitudinal acceptance
- No beam loss
- No transverse or longitudinal rms emittance growth

Transverse and longitudinal rms emittances along the SC linac




Horizontal, vertical and longitudinal phase spaces at the exit of the SC linac



High Energy Beam Transport – [1]

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY



Cryomodule #4
single $\lambda/4$ cavity
 $\beta_{\text{opt}}=0.041$


- Achieve the required beam conditions on target
- π -phase advance cell
 - 4 quadrupoles
- Cryomodule
 - Single $\lambda/4$ cavity, $\beta_{\text{opt}}=0.041$
 - Used as rebuncher
- Final focusing
 - 4 quadrupoles
 - Superconducting solenoid

High Energy Beam Transport – [2]


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- RIBs accelerated to ~ 3.0 MeV/u
- $\sim 88\%$ of the RIBs within 1 ns and 1 keV/u

Horizontal, vertical
and longitudinal
phase spaces on
target



Energy spread and
bunch width on
target




High Energy Beam Transport – [3]


MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- RIBs decelerated to ~ 0.3 MeV/u
 - $\sim 89\%$ of the RIBs within 1 ns and 1 keV/u

Horizontal, vertical
and longitudinal
phase spaces on
target




Energy spread and
bunch width on
target



Future Upgrades Possible

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- **Phase I: 0.3 ~ 3.0 MeV/u – In progress**
- **Upgrades: 0.3 ~ 12 MeV/u**
 - Additional SRF cryomodules
 - NSCL High Bay Area expansion
 - New experimental areas



MSU Reaccelerator - Status

MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY MICHIGAN STATE UNIVERSITY

- **Baseline accelerator system defined**
- **End-to-end beam simulations performed**
- **RFQ construction expected to be complete in 2009**
- **Superconducting cavity & cryomodule prototyping
- test and design ongoing**
- **Experimental apparatus planning - underway**
- **Studies of beam diagnostics and realistic beam
tuning scenarios - ongoing**

Planned Low-Energy RIB Facility at the NSCL

- R&D for gas stoppers, EBIT charge-breeder - on going
- The project expected to complete by 2009
- Will be the first facility of creating fast RIBs in-flight, stopping, charge-breeding, and re-accelerating them efficiently and with minimum loss

